

Natural gas generator set								
50Hz (1500RPM)\400V/230V								
Model	Standby Power (KW)	Prime Power (KW)	Engine Model	Displacement/ Cylinder	Gas consumption at 100% Load (m³/h)	Electrical efficiency (%)	Opentype Dimention (mm)	Dry weight
AS14NG	11	10	F10A-NG	1.0(4)	3.8	27	1200*760*850	320
AS17NG	13.2	12	F10A-NG	1.1(4)	4.56	27	1200*760*850	320
AS21NG	16.5	15	4Y-NG	2.2(4)	5.7	27	1400*710*920	420
AS28NG	22	20	4Y-NG	2.2(4)	7,6	27	1400*710*920	450
AS28NG	22	20	4JB1-NG	2.8(4)	7	27	1500*600*980	550
AS35NG	27.5	25	4Y-NG	2.2(4)	8.75	28.5	1400*710*920	500
AS35NG	27.5	25	4JB1T-NG	2.8(4)	8.75	28.3	1500*600*980	600
Cummins Gas genset								
ASC35NG	27.5	25	4B3.9-NG	3.9(4)	8	31	1850*1000*1350	900
ASC41NG	33	30	4BT3.9-NG	3.9(4)	9.6	31	1850*1000*1350	980
ASC50NG	40	36	4BTA3.9-NG	3.9(4)	11.2	33	1850*1000*1350	1010
ASC55NG	44	40	4BTAA3.9-NG	3.9(4)	12.4	33	1850*1000*1350	1080
ASC83NG	66	60	6BTA5.9-NG	5.9(6)	19.8	30	2200*1000*1400	1200
ASC104NG	83	75	6BTAA5.9-NG	5.9(6)	23.2	32	2200*1000*1400	1400
ASC118NG	93	84	6BTAA5.9-NG	5.9(6)	25.2	33	2200*1000*1400	1450
ASC131NG	105	95	6CTAA8.3-NG	8.3(6)	29.45	32	2400*1150*1500	1650
ASC144NG	115	104	6CTAA8.3-NG	8.3(6)	31.2	33	2400*1150*1500	1860
ASC165NG	132	120	6CTAA8.3-NG	8.3(6)	36	33	2400*1150*1500	2000
ASC220NG	175	160	NTA855-NG	14(6)	56	29	2900*1160*1900	2420
ASC247NG	200	182	NTAA855-NG	14(6)	58.5	33	2900*1160*1900	3300
ASC275NG	220	200	NTAA855-NG	14(6)	64	33	2900*1160*1900	3650
ASC344NG	275	250	KTAA19-NG	18.9(6)	82.5	32	3800×1550×2000	3850
ASC385NG	308	280	KTAA19-NG	18.9(6)	90	36	4000×1550×2000	4000
ASC413NG	330	300	KTAA19-NG	18.9(6)	96	36	4000×1550×2000	4000
ASC550NG	440	400	KTAA38-NG	38(12)	132	34	4510×1850×2400	7500
ASC618NG	495	450	KTAA38-NG	38(12)	144	35	4510×1850×2400	8000
ASC688NG	550	500	KTAA38-NG	38(12)	160	35	4510×1850×2400	8500
Deutz Gas Genset								
ASD220NG	176	160	BF6M1015-NG	11.9(6)	55	34	2620*1160*1810	2500
ASD247NG	200	182	BF6M1015-NG	11.9(6)	62	34	2620*1160*1810	2500
ASD325NG	260	240	BF8M1015-NG	15.8(8)	82	34	3380*1340*1890	3000
ASD413NG	330	300	TBD234V12-NG	21.6(12)	102	34	3800*1250*1850	4000
ASD475NG	380	350	TBD604L6-NG	26.6(6)	119	34	3988*1550*2069	5000
ASD625NG	/	500	TBD620V8-NG	35.4(8)	132	38	4015*1450*2480	8800
ASD1000NG	/	800	TBD620V12-NG	53.2(12)	232.9	37	4500*1700*2480	10050
ASD1375NG	/	1100	TBD620V16-NG	70.8(16)	317.9	37	5200*1700*2353	12600
Continuous Power								
ASM44NG		35	E0834 E312	4.6(4)	11	33	1400*710*920	480
ASM66NG		53	E0836 E312	6.9(4)	15	37	1950*1000*1450	580
ASM80NG		64	E0834 LE302	4.6(4)	18	37	2280*1050*1500	1000
ASM130NG		104	E0836 LE202	6.9(6)	28	37	3090*1170*1560	3250
ASM250NG		200	E2876 LE302	12.8(6)	54	37	3720*1300*1850	3800
ASM315NG		252	E2848 LE322	14.6(8)	68	38	3950*1532*1671	4850
ASM500NG		400	E2842 LE322	21.9(12)	105	39	4050*1532*1671	5900
ASM625NG		500	E3262LE202	21.9(12)	131	40	4250*1532*1671	6100
ASP383NG		306	4006-23TRS1	22.921(6)	85	37	4646*1992*2189	6056
ASP468NG		374	4006-23TRS2	22.921(6)	101	38	4646*1992*2189	6056
ASP531NG		425	4008-30TRS1	30.561(8)	116	38	5540*1992*2283	7485
ASP625NG		500	4008-30TRS2	30.561(8)	135	39	5540*1992*2283	7485
ASP1094NG		875	4016-61TRS1	61.123(16)	237	38	4641*1836*2148 *	10120
ASP1250NG		1000	4016-61TRS1	61.123(16)	268	39	4641*1836*2148*	10120

Also available in the following voltages: 440/254V,415/240V,380/220V,220/115,200/115V,6600V,10000V. *Without Radiator